

AD-A170 253

THE INFLUENCE OF FLUCTUATIONS IN ACOUSTIC TRAVEL TIME ON  
LOCATING THE POSI (U) SACLANT ASM RESEARCH CENTRE LA  
SPEZIA (ITALY) T KNUDSEN ET AL OCT 85

1/1


UNCLASSIFIED

SACLANTCEN-SM-184

F/G 17/1

NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

12

SACLANTCEN Memorandum SM - 184  
SACLANTCEN Memorandum SM - 184

SACLANTCEN Memorandum SM - 184

SACLANT ASW  
RESEARCH CENTRE  
MEMORANDUM




AD-A170 253

THE INFLUENCE OF FLUCTUATIONS IN  
ACOUSTIC TRAVEL TIME  
ON LOCATING THE POSITION OF  
AN UNDERWATER SOUND SOURCE

by  
Tor KNUDSEN  
Angelo LOMBARDI

DTIC FILE COPY



OCTOBER 1985

NORTH  
ATLANTIC  
TREATY  
ORGANIZATION

SACLANTCEN  
LA SPEZIA, ITALY

This document is unclassified. The information it contains is published subject to the conditions of the legend printed on the inside cover. Short quotations from it may be made in other publications if credit is given to the author(s). Except for working copies for research purposes or for use in official NATO publications, reproduction requires the authorization of the Director of SACLANTCEN.

86 7 28 010

DISTRIBUTION STATEMENT A  
Approved for public release  
Distribution Unlimited

This document is released to a NATO Government at the direction of the SACLANCEN subject to the following conditions:

1. The recipient NATO Government agrees to use its best endeavours to ensure that the information herein disclosed, whether or not it bears a security classification, is not dealt with in any manner (a) contrary to the intent of the provisions of the Charter of the Centre, or (b) prejudicial to the rights of the owner thereof to obtain patent, copyright, or other like statutory protection therefor.

2. If the technical information was originally released to the Centre by a NATO Government subject to restrictions clearly marked on this document the recipient NATO Government agrees to use its best endeavours to abide by the terms of the restrictions so imposed by the releasing Government.

*Published by*



TABLE OF CONTENTS

	<u>Pages</u>
ABSTRACT	1
INTRODUCTION	1
1 MATHEMATICAL MODEL	2
2 OPTIMUM RELATIVE RECEIVER POSITION	3
3 SIMULATION	7
4 RANDOM PERTURBATIONS OF THE TRAVEL TIMES	8
5 RANDOM PERTURBATION OF SOUND SPEED	8
CONCLUSION	9
REFERENCES	9

List of Figures

1. Definition of coordinates.	2
2. Optimum receiver positions.	6
3. Receivers placed on a line.	11
4. Receivers placed at an angle.	13
5. Receivers placed in the apices of a triangle.	15



Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
<b>PER LETTER ON FILE</b>	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
<b>A-1</b>	

NORTH ATLANTIC TREATY ORGANIZATION

SACLANT ASW Research Centre  
Viale San Bartolomeo 400,  
I-19026 San Bartolomeo (SP), Italy.

tel: national 0187 540111  
international + 39 187 540111  
telex: 271148 SACENT I

THE INFLUENCE OF FLUCTUATIONS IN  
ACOUSTIC TRAVEL TIME  
ON LOCATING THE POSITION OF  
AN UNDERWATER SOUND SOURCE

by

Tor Knudsen  
Angelo Lombardi


October 1985

This memorandum has been prepared within the SACLANTCEN  
Systems Research Division as part of Project 22.

*T.G. Goldsberry*  
T.G. GOLDSBERRY  
Division Chief

DTIC  
ELECTE  
JUL 28 1986  
S B D

DISTRIBUTION STATEMENT A  
Approved for public release  
Distribution Unlimited



THE INFLUENCE OF FLUCTUATIONS IN ACOUSTIC TRAVEL TIME  
ON LOCALIZING THE POSITION OF AN UNDERWATER SOURCE

by

Tor Knudsen and Angelo Lombardi

ABSTRACT

This paper investigates the accuracy of an underwater acoustic positioning system in locating a sound source that transmits at unknown times in conditions in which the acoustic travel times between source and receivers fluctuate widely. The system uses three omnidirectional receivers. The accuracy of the system depends very much on the relative positions of these receivers. With well-chosen relative receiver dispositions, the position of a sound source at 20 km range can be located within  $\pm 150$  m, even with fluctuations in travel time of as high as  $\pm 100$  ms.

INTRODUCTION

The need to locate the position of a sound source in shallow water by means of three omnidirectional receivers led to an experimental investigation of the fluctuations in travel time between transmission and reception of the sound. This showed that, in severe multipath conditions, the travel time could vary by about  $\pm 65$  ms between transmissions. The fluctuations were so rapid that two transmissions 150 s apart could show a difference in travel time of about 130 ms [1]. If one knows when the transmission took place, this gives an error of only about 200 m in locating the position of the sound source. However, if it is not known when the transmission took place, the computation of the source's position must be based on the differences in the arrival times of the same signal at three points spaced some distance apart. The existence of fairly large fluctuations in the travel times themselves means that such fluctuations will have a large influence on the accuracy of locating the position of the source.

This paper investigates the effect of different magnitudes of travel-time fluctuation on the accuracy of the computed position of the sound source. It also shows how the effect of the fluctuations can be reduced by placing the receivers in optimum relative positions.



1 MATHEMATICAL MODEL

In the models the receivers are positioned as shown on Fig. 1 at  $(x_1, y_1)$ ,  $(x_2, y_2)$ ,  $(x_3, y_3)$ . The source transmits a signal at time  $t$ , which is received at the three receivers at times  $t_1$ ,  $t_2$  and  $t_3$ . We therefore find:

$$\begin{aligned} (1/c) \sqrt{(x-x_1)^2 + (y-y_1)^2} &= t_1 - t \\ (1/c) \sqrt{(x-x_2)^2 + (y-y_2)^2} &= t_2 - t \\ (1/c) \sqrt{(x-x_3)^2 + (y-y_3)^2} &= t_3 - t \end{aligned} \quad , \quad (\text{Eq. 1})$$

where  $c$ , the sound speed, is assumed to be constant and independent of depth, and the sound is assumed to travel in straight paths. In fact the sound rays are bent in response to the sound-speed profile; this can be compensated for by modifying the sound speed used in these calculations. From Eq. 1 we eliminate the unknown  $t$  and get

$$\begin{aligned} t_2 - t_1 &= (1/c) \left[ \sqrt{(x-x_2)^2 + (y-y_2)^2} - \sqrt{(x-x_1)^2 + (y-y_1)^2} \right] \\ t_3 - t_1 &= (1/c) \left[ \sqrt{(x-x_3)^2 + (y-y_3)^2} - \sqrt{(x-x_1)^2 + (y-y_1)^2} \right] \end{aligned} \quad (\text{Eq. 2})$$

or, as matrix equation

$$Y = m(x, y) \quad , \quad (\text{Eq. 3})$$

where

$$Y = \begin{bmatrix} t_2 - t_1 \\ t_3 - t_1 \end{bmatrix}$$

$$X = \begin{bmatrix} x \\ y \end{bmatrix}$$

and  $m(x, y)$  is the right-hand side of Eq. 2.




FIG. 1 DEFINITION OF COORDINATES

2 OPTIMUM RELATIVE RECEIVER POSITION [2]

We want to estimate the position of the sound source

$$x_k^T = [x, y]_{t=t_k}$$

from a series of observations of the differences in time between the acoustic transmission and the reception at the three receivers. The mathematical model for this is given in App. 7A of Jazwinsky [3]:

$$y_i = M(i) \phi(i, k) x_k + v_i, \quad i=1, \dots, k, \quad (\text{Eq. 4})$$

where  $\{v_i\}$  is a white, but not necessarily gaussian, vector sequence with

$$E\{v_i\} = 0 \quad \text{and} \quad E\{v_i v_j^T\} = R_i \delta_{ij}, \quad R_i > 0,$$

and  $\phi(i, k)$  is the state transition matrix.

The parameter  $x_k$  may be viewed as the state at time  $t_k$  of the dynamical system

$$x_{i+1} = \phi(i+1, i) x_i \quad (\text{Eq. 5})$$

$$y_i = M(i) x_i + v_i, \quad (\text{Eq. 6})$$

where  $y_i$  is the measurement at time  $t_i$ .

We want to find the estimate  $\hat{x}_k$  that minimizes the error variance

$$E\{(x_k - \hat{x}_k)^T (x_k - \hat{x}_k)\} = \text{tr } E\{(x_k - \hat{x}_k)(x_k - \hat{x}_k)^T\}. \quad (\text{Eq. 7})$$

It can be shown [2] that the linear, unbiased minimum variance estimate  $\hat{x}_k$  of  $x_k$  has a covariance matrix given by

$$E\{(x_k - \hat{x}_k)(x_k - \hat{x}_k)^T\} = \mathcal{F}_{k,1}^{-1}, \quad (\text{Eq. 8})$$

where

$$\mathcal{F}_{k,1} = \sum_{i=1}^k \phi^T(i, k) M^T(i) R_i^{-1} M(i) \phi(i, k) \quad (\text{Eq. 9})$$

is the information matrix.

So minimizing the error variance is equivalent to minimizing  $\text{tr } \mathcal{F}_{k,1}^{-1}$  or maximizing the determinant  $|\mathcal{F}_{k,1}|$ .

In our case the sound source does not move, so that

$$\Phi(i+1, i) = \Phi = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} = I$$

and  $\mathcal{F}_{k,1}$  reduces to

$$\mathcal{F}_{k,1} = \sum_{i=1}^k M^T(i) R_i^{-1} M(i) = \sum_{i=1}^k W_i, \quad (\text{Eq. 10})$$

so that we shall maximize

$$|W_i| = |R_i^{-1}| |M(i)|^2. \quad (\text{Eq. 11})$$

Comparing Eqs. 3 and 6 we see that the actual observation describes a nonlinear relation between the source's position and the measured time difference. Equation 6 can be found from Eq. 3 by linearization.

$$M = \begin{bmatrix} \frac{\partial m_{11}(x,y)}{\partial x} & \frac{\partial m_{12}(x,y)}{\partial y} \\ \frac{\partial m_{21}(x,y)}{\partial x} & \frac{\partial m_{22}(x,y)}{\partial y} \end{bmatrix} = \begin{bmatrix} M_{11} & M_{12} \\ M_{21} & M_{22} \end{bmatrix}, \quad (\text{Eq. 12})$$

where

$$M_{11} = \frac{1}{c} \left\{ \frac{x-x_2}{\sqrt{(x-x_2)^2 + (y-y_2)^2}} - \frac{x-x_1}{\sqrt{(x-x_1)^2 + (y-y_1)^2}} \right\}$$

$$M_{12} = \frac{1}{c} \left\{ \frac{y-y_2}{\sqrt{(x-x_2)^2 + (y-y_2)^2}} - \frac{y-y_1}{\sqrt{(x-x_1)^2 + (y-y_1)^2}} \right\}$$

$$M_{21} = \frac{1}{c} \left\{ \frac{x-x_3}{\sqrt{(x-x_3)^2 + (y-y_3)^2}} - \frac{x-x_1}{\sqrt{(x-x_1)^2 + (y-y_1)^2}} \right\}$$

$$M_{22} = \frac{1}{c} \left\{ \frac{y-y_3}{\sqrt{(x-x_3)^2 + (y-y_3)^2}} - \frac{y-y_1}{\sqrt{(x-x_1)^2 + (y-y_1)^2}} \right\}$$

But referring to Fig. 1 we now find that  $M$  is also given by

$$M = \frac{1}{c} \begin{bmatrix} \cos \theta_2 - \cos \theta_1 & \sin \theta_2 - \sin \theta_1 \\ \cos \theta_3 - \cos \theta_1 & \sin \theta_3 - \sin \theta_1 \end{bmatrix}, \quad (\text{Eq. 13})$$

where  $\theta_1$ ,  $\theta_2$  and  $\theta_3$  are the angles defined in Fig. 1.

If we measure the arrival times with a variance  $\sigma_t^2$  we find that

$$R = \begin{bmatrix} 2\sigma_t^2 & \sigma_t^2 \\ \sigma_t^2 & 2\sigma_t^2 \end{bmatrix}$$

and thus

$$R^{-1} = \frac{1}{3\sigma_t^2} \begin{bmatrix} 2 & -1 \\ -1 & 2 \end{bmatrix},$$

and Eq. 11 then becomes

$$|W_f| = \frac{1}{3\sigma_t^4 c^4} \{ \sin(\theta_1 - \theta_3) - \sin(\theta_2 - \theta_3) + \sin(\theta_2 - \theta_1) \}^2. \quad (\text{Eq. 14})$$

To maximize Eq. 14 we apply the Lagrangian multiplier method with the conditional function

$$\phi(\Delta) = \Delta_1 - \Delta_2 + \Delta_3 = 0, \quad (\text{Eq. 15})$$

where

$$\Delta_1 = (\theta_1 - \theta_3)$$

$$\Delta_2 = (\theta_2 - \theta_3)$$

$$\Delta_3 = (\theta_2 - \theta_1)$$

and the additional function

$$Z(\Delta) = |W_i| + \lambda \phi(\Delta) \quad . \quad (\text{Eq. 16})$$

Setting its partial derivatives to zero gives the following condition

$$\Delta_1 = \Delta_2$$

$$\Delta_2 = \Delta_3$$

$$\Delta_1 = \Delta_3 \quad .$$

Substituting these in Eq. 15 we find that

$$\Delta_1 = \Delta_2 \quad \text{gives} \quad \Delta_3 = 0$$

$$\Delta_2 = \Delta_3 \quad \text{gives} \quad \Delta_1 = 0$$

$$\Delta_1 = \Delta_3 \quad \text{gives} \quad \Delta_2 = 2\Delta_1 \quad ,$$

where the last solution obviously is the maximum. Substituting  $\Delta_1 = \Delta_3 = \Delta_2/2$  in Eq. 14 and maximizing with respect to  $\Delta_2$  gives

$$\Delta_2 = 240^\circ$$

and

$$\Delta_1 = \Delta_3 = 120^\circ \quad .$$

The optimum relative receiver positions are therefore in the shape of a triangle enclosing the source and such that the angle subtended by each leg of the triangle is  $120^\circ$ , as shown in Fig. 2.




FIG. 2 OPTIMUM RECEIVER POSITIONS

### 3 SIMULATION

A simulation program was developed to determine how different receiver geometries would influence the accuracy in locating the position of a sound source. The program computes the theoretical travel time between the source and the receivers and perturbrates these delays with random values drawn from uniform distributions. The position resulting from these perturbed travel times is then computed, and the process repeated with another set of random numbers in order to plot the error distribution in two dimensions.

Assuming that the real position of the source is  $(x_0, y_0)$ , Eq. 1 is used to compute the theoretical travel times. The arrival times  $t_1$ ,  $t_2$  and  $t_3$  are then perturbed according to

$$\begin{aligned} d_1 &= t_1 + s U[-1,1] \\ d_2 &= t_2 + s U[-1,1] \\ d_3 &= t_3 + s U[-1,1] \quad , \end{aligned} \quad (\text{Eq. 17})$$

where  $s$  is a constant used for scaling and  $U[-1,1]$  means a number drawn from a uniform distribution of random numbers between -1 and 1.

Equation 2 describes the relationship between the position of the source and the measured travel-time differences. Since it is nonlinear, we start by linearizing around the actual position  $X_0$ , which gives travel-time differences of

$$Y_0 = \begin{bmatrix} t_2 - t_1 \\ t_3 - t_1 \end{bmatrix}$$

$$Y - Y_0 = M(X - X_0) \quad ,$$

so that

$$X - X_0 = M^{-1}(Y - Y_0) = M^{-1} \begin{bmatrix} d_2 - d_1 - (t_2 - t_1) \\ d_3 - d_1 - (t_3 - t_1) \end{bmatrix} \quad ,$$

where  $M$  is given by Eq. 12.

The estimated position due to the perturbed travel time is

$$X = M^{-1}(Y - Y_0) + X_0 \quad . \quad (\text{Eq. 18})$$

We then compute the new travel times using  $X$  in Eq. 1 and relinearize  $M$  around the new position estimate  $X$ . Using Eq. 18 we then compute a better estimate.

The iteration is ended when the new and the previously iterated positions are within a chosen limit, usually set to 5 m. The simulation is then repeated for another set of random perturbations by returning to Eq. 17.

#### 4 RANDOM PERTURBATIONS OF THE TRAVEL TIMES

The computer program was run on several examples in order to investigate how the relative positions of the receivers influenced the error in estimating the sound source's position. The distance between the outermost receivers was 20 km and the sound source was moved to different positions within a square of 30 km  $\times$  30 km dimensions. Figure 3 shows the results for the three mean propagation delays of  $\pm 25$  ms,  $\pm 50$  ms and  $\pm 100$  ms when the receivers were placed along the  $y$  axis at 10 km intervals; because the errors are symmetric around a line that is parallel to the  $x$  axis and crosses the  $y$  axis at 10 km, only half the field is shown.

It is seen from the figure that the uncertainties in the position of each sound source are ellipses centred around its real position, which is marked with a cross. The error in the estimated position increases very much when the independent fluctuations in the time of arrival of the signal at the three receivers increase from  $\pm 25$  ms to  $\pm 100$  ms. At 20 km range (same distance as the receiver baseline) the maximum error has increased from about  $\pm 1$  km to about  $\pm 3.5$  km.

The situation is greatly improved when the receivers are positioned in a right angle, as shown in Fig. 4 for the same three mean propagation delays. The distance between the outermost receivers is again 20 km and it is seen that even with uniform random fluctuations of  $\pm 100$  ms in the time of arrival the maximum error is within  $\pm 500$  m for a sound source 20 km from the furthest receiver.

The optimum relative receiver disposition was found earlier to be as depicted in Fig. 2. The results of placing the receivers in this configuration are shown in Fig. 5 for the same three mean propagation delays. It is seen that the errors within the triangle formed by the receivers are very small (within  $\pm 150$  m), even with  $\pm 100$  ms time fluctuation. However, when the sound source is placed outside the triangle the errors start to increase considerably.

#### 5 RANDOM PERTURBATION OF SOUND SPEED

Normally one may not know the sound speed accurately, or it may vary along the path from the sound source to the receiver and also between the paths to the different receivers. This effect can be interpreted as a range-dependent fluctuation in the acoustic travel times between source and receivers. To give a feeling for the problem we assume that there is an

uncertainty in the actual sound speed, given by  $(1500 \pm 5)$  m/s. This results in an uncertainty of  $\pm 50$  ms in travel time for distances between source and receivers that are greater than  $x$ , given by

$$x = \frac{0.05 \times 1500 \times 1505}{5} = 22 \text{ km}$$

Since the uncertainty in the sound speed can be interpreted as an uncertainty in acoustic travel times, the positioning error depends, as before, on the relative position of the receivers.


### CONCLUSION

This paper shows that even with fluctuation in acoustic travel times of the order of  $\pm 100$  ms it is possible to locate the position of a sound source at 20 km range within  $\pm 150$  m by proper relative positioning of three omnidirectional receivers.


### REFERENCES

1. KNUDSEN, T. Measurements of correlation loss and time-spreading in linear fm sweeps and pseudo-random noise signals transmitted over long ranges in shallow water, SM- (In preparation). La Spezia, Italy, SACLANT ASW Research Centre, 1984.
2. ASSELT, Henk van. SACLANT ASW Research Centre, La Spezia, Italy. Private communication, 1982.
3. JAZWINSKY, A.H. Stochastic processes and filtering theory. New York, NY, Academic Press, 1970.





a



b






FIG. 3 RECEIVERS PLACED ON A LINE.  
 Uncertainty in position due to fluctuation in propagation delay of  
 a)  $\pm 25$  ms  
 b)  $\pm 50$  ms  
 c)  $\pm 100$  ms








FIG. 4 RECEIVERS PLACED AT AN ANGLE.  
 Uncertainty in position due to fluctuation in propagation delay of  
 a)  $\pm 25$  ms  
 b)  $\pm 50$  ms  
 c)  $\pm 100$  ms






FIG. 5 RECEIVERS PLACED IN THE APICES OF A TRIANGLE.  
 Uncertainty in position due to fluctuation in propagation delay of  
 a)  $\pm 25$  ms  
 b)  $\pm 50$  ms  
 c)  $\pm 100$  ms

KEYWORDS

ACOUSTIC POSITIONING SYSTEM  
ACOUSTIC TRAVEL TIME  
FLUCTUATION  
MULTIPATH CONDITIONS  
OMNIDIRECTIONAL RECEIVER  
PERTURBATED TRAVEL TIME  
PROPAGATION DELAY  
SOUND SOURCE  
SOUND-SPEED PROFILE

INITIAL DISTRIBUTION

<u>MINISTRIES OF DEFENCE</u>		<u>SCNR FOR SACLANTCEN</u>	
	Copies		Copies
JSPHQ Belgium	2	SCNR Belgium	1
DND Canada	10	SCNR Canada	1
CHOD Denmark	8	SCNR Denmark	1
MOD France	8	SCNR Germany	1
MOD Germany	15	SCNR Greece	1
MOD Greece	11	SCNR Italy	1
MOD Italy	10	SCNR Netherlands	1
MOD Netherlands	12	SCNR Norway	1
CHOD Norway	10	SCNR Portugal	1
MOD Portugal	2	SCNR Turkey	1
MOD Spain	2	SCNR U.K.	1
MOD Turkey	5	SCNR U.S.	2
MOD U.K.	20	SECGEN Rep. SCNR	1
SECDEF U.S.	65	NAMILCOM Rep. SCNR	1
 <u>NATO AUTHORITIES</u>		 <u>NATIONAL LIAISON OFFICERS</u>	
Defence Planning Committee	3	NLO Canada	1
NAMILCOM	2	NLO Denmark	1
SACLANT	10	NLO Germany	1
SACLANTREPEUR	1	NLO Italy	1
CINCWESTLANT/COMOCEANLANT	1	NLO U.K.	1
COMSTRIKFILTANT	1	NLO U.S.	1
COMIBERLANT	1		
CINCEASTLANT	1	<u>NLR TO SACLANT</u>	
COMSUBACLANT	1	NLR Belgium	1
COMMAIREASTLANT	1	NLR Canada	1
SACEUR	2	NLR Denmark	1
CINCNORTH	1	NLR Germany	1
CINCSOUTH	1	NLR Greece	1
COMNAVSOUTH	1	NLR Italy	1
COMSTRIKFORSOUTH	1	NLR Netherlands	1
COMEDCENT	1	NLR Norway	1
COMMARAIRED	1	NLR Portugal	1
CINCHAN	3	NLR Turkey	1
		NLR UK	1
		NLR US	1
		Total initial distribution	246
		SACLANTCEN Library	10
		Stock	24
		Total number of copies	280



END

DTIC

9-86